



HOME NICE

SPC FLOORING
Waterproof Flooring



SPC CLICK FLOORING

Rigid Core LVT CLICK

Dimension

Construction	New Generation of Luxury Vinyl Tiles, mixture by Natural Limestone Powder, polyvinyl chloride, stabilizer etc. Density 2000kg/m3
Thickness	7+1.5
Wear Classification	0.7mm
Surface structure	Deep embossed
Edge type	Micro Bevel
Locking system	2G

TECHNICAL SPECIFICATION

Item	Standard	Result	
Overall Thick	EN ISO 24236	±0.15mm	
Wearlayer Thick	EN ISO 24340	±0.05mm	
Dimensional Stability after exposure to heat	EN ISO 24342	X Direction: 0.05%	Y Direction: 0.015%
Curling after exposure to heat	EN 434	<0.2mm	
Peeling Strength	EN 431	>90N(50mm)	
Locking Strength	EN ISO 24334	>120N(50mm)	
Residual Indentation	EN ISO 24343.1	<0.1mm	
Castor Chair	ISO 4918	After 25000 cycles, no	visible damage
Slip Resistance	EN 13893	Class DS	
Fire Resistance	EN 13501.1	Bfl - S1	
Abrasion Resistance	EN 660	Group T	
Stain & Chemical Resistance	EN ISO 26987	Class 0	
Cigarette Burn Test	EN ISO 1399	Class 4	
Color Fastness	ISO 105-B02	≥Grade 6	
Formaldehyde Emission	EN 717.3	0	



HE9001



HE9002



HE9003



HE9004





HE9005



HE9006



HE9007



HE9008

