



SINDA FLOORING



SPC CLICK FLOORING

1524x230x8.0mm
0.7mm Wearlayer
(6.0 SPC+2.0 IXPE)



SPC CLICK FLOORING

Construction	Mixture by Natural Limestone Powder, Polyvinyl Chloride, Stabilizer etc.
Specification	1524x230x8.0mm
Thickness	6+2 IXPE
Wearlayer	0.7mm
Surface Structure	Wood Embossing
Edge Type	Bevel Edge
Density	2.0g/cm ³
Locking System	Angle Angle

TECHNICAL SPECIFICATION

Item	Standard	Result
Reaction to fire	EN 14041:2004	class Bf1-s1
Formaldehyde emission	EN 14041:2004	class E1
Slip resistance	EN 14041:2004	class DS
Dimensional stability	ISO23999:2021	X Direction: 0.05% Y Direction: 0.08%
Curling	ISO23999:2021	0.5mm
Residual indentation	ISO24343-1:2007	0.1mm
Impact Sound Improvement	ISO 10140-3:2021	△Lw =21 dB
VOC	ISO16000-3:2011	A+
SVHC	Reach No 1907/2006	Pass
Light stability	ISO 105-B02	≥6
Castor chair	EN 4918:2016	After 25000 cycles, no visible damage
Slip resistance	DIN 51130: 2014-02	R10
Wear resistance	EN 660-2	Group T
Thermal resistance	EN 12667:2001	0.041m²K/W
Determination of resistance to stains chemical resistance	ISO26987:2008	Resistant
Squareness	ISO24342:2018	Deviation range: X Direction: +0.05mm Y Direction: +0.05mm
Straightness	ISO24342:2018	Deviation range: X Direction: +0.05mm Y Direction: +0.05mm
Peel resistance	ISO 24345:2006	X Direction: 65N/50mm Y Direction: 65N/50mm



 SINDA FLOORING



SD 002



SD 006



SD 008



SD 012





SD 013



SD 014



SD 015



SD 016